

RhinoAg: Single Spindles

TW30 SERIES



Full length replaceable skid shoes



Tapered side skirts to help prevent gouging



3" Cut Capacity



Smooth top deck



Available in 60" and 72" cutting widths



High capacity cutting chamber

RHINOAG

TW30 SERIES

Specifications	TW35	TW36	TW37
Cutting Width:	60"	72"	84"
Overall Width:	66 1/2"	78 1/2"	90 1/2"
Overall Length:	105"	121"	136"
Cutting Height (Min):	1 1/2"		
Hitch:	CAT 1/ CAT 2 Std. CAT 1/ CAT 2 Q.H. iMatch™**		CAT 2/ CAT 3 Std. CAT 2/ CAT 3 Q.H.
Blade Carrier:	Infinity - Cast		Infinity - Steel
Blades:	1/2" x 4" Updraft		
PTO HP Required (Min):	35	45	60
Gearbox Rating*:	130 HP		210 HP
Blade Tip Speed (FPM):	14,497 (540 RPM)	14,854 (540 RPM)	15,667 (540 RPM) 15,993 (1000 RPM)
Cutting Capacity:	3"		
Driveline Size:	CAT 4		
Driveline Protection:	Slip Clutch		
Deck Thickness:	10 Ga		
Side Skirt:	1/4"		
Tail Wheel:	Single		Dual
Tire and Wheel:	4" x 8" Laminated		(2) 4" x 8" Laminated
Safety Deflector:	Deflectors or Chains		Chains
Weight (Approx): w/ Rubber Deflectors w/ Chains	920 lbs 975 lbs	1075 lbs 1140 lbs	1,500 lbs 1,600 lbs

*Gearbox power rating based on actual field performance.

**iMatch is a trademark of Deere & Company.

