

RhinoAg: **Single Spindles**

▶ **TW10 SERIES**



Dependable performance at a competitive price



Powder coated paint for maximum durability and a great look



1" material cut capacity



Offered in 4', 5' and 6' cutting widths



Perfect for cutting around the farm, ranch, or homestead



Available with sheer bolt or slip clutch protection

RHINOAG

TW10 SERIES

Specifications	TW14	TW15	TW16
Cutting Width	4' (48")	5' (60")	6' (72")
Overall Width	52 1/2"	64"	76 1/4"
Overall Length	87"	99"	111"
Cutting Height (Min)	1 1/2"		
Hitch	CAT 1 - Std		
Blade Carrier	Infinity - Steel		
Blades	1/2" x 3"		
PTO HP Required (Min)	20		25
Gearbox Rating*	60 HP		
Blade Tip Speed (FPM)	15,608	16,117	14,963
Cutting Capacity	1"		
Driveline Size	CAT 3		
Driveline Protection	Shear Bolt or Slip Clutch		
Deck Thickness	12 Ga		
Side Skirt	10 Ga		
Tire and Wheel	3.75" x 15" Solid Rubber Tire		
Safety Deflector	Front Belt / Rear Steel Band		
Weight (Approx)	460 lbs	530 lbs	630 lbs

*Gearbox power rating based on actual field performance.

