

RhinoAg: Landscape

REBEL SERIES



Designed for use on 25-65 PTO HP tractors



Metal debris deflector (Reverse model only)



5 year limited gearbox warranty and 1 year machine warranty



CAT 1 Standard and QH (5 & 6 ft models),
CAT 1 & 2 Standard and QH (7 ft model)



Six Hardened "L" blades per rotor flange



Hitch extension kit available on the REB60
and REB72 models.



Cast iron gearbox housing



1/2" steel end plates



Front-to-rear hitch points are continuously
welded to the mainframe



Strong "all gear" drivetrain featuring double lip
seals on each end of the rotor shaft

RHINOAG

REBEL SERIES

Specifications	STANDARD			REVERSE		
	REB60	REB72	REB84	REB60R	REB72R	REB84R
Tilling Width:	59"	70.5"	82.5"	59"	70.5"	82.5"
Overall Width:	66"	78"	90"	66"	78"	90"
Tilling Depth (Max.):*	7-1/2"					
Hitch:	CAT 1 (Std) / CAT 1 QH		CAT 1 & 2 (Std) CAT 1 & 2 QH	CAT 1 (Std) / CAT 1 QH		CAT 1 & 2 (Std) CAT 1 & 2 QH
Knife Type:	“L”					
Number of Knives:	42	54	66	42	54	66
Number of Flanges:	7	9	11	7	9	11
Recommended PTO HP (Min/Max):	25 / 45 HP	35 / 55 HP	45 / 65 HP	25 / 45 HP	35 / 55 HP	45 / 65 HP
Rotor Speed:	211 RPM					
Driveline Size:	CAT 4					
Driveline Protection:	Slip Clutch					
Gearbox Housing:	Cast					
End Plate Thickness:	1/2"					
Rotor/ Blade Rotation Dia:	17"					
Rotor Shaft Dia:	3"					
Rotor Drive Type:	Gear Driven					
Tine Rotation:	Standard			Reverse		
Weight (Approx.):	673 lbs.	747 lbs.	817 lbs.	683 lbs.	759 lbs.	831 lbs.

*Requires multiple passes



WARRANTY

5 year limited gearbox and
1 year machine warranty.



HITCH FRAME

continuously welded to main frame for
maximum strength.



1/2" END PLATES

absorb the demands of the job

