

Rhino Ag: **Flex-Wings**

▶ **TS10**



Fits Through Gates as Narrow as 8'



Average Mowing Time of 4 MPH



Walterscheid Ez-Loc Collar Makes Hookup Easy



Smooth, Quiet Operation



Replaceable Skid Shoes for Simple Maintenance



Heavy-Duty Turn Buckles for Fewer Breakdowns and Less Stress

**RHINOAG**

# TS10

Specifications	TS10
Cutting Width:	120"
Transport Width:	93"
Transport Height:	68"
Overall Width:	126"
Overall Length:	162"
Cutting Height: *	1" - 15"
Self-Leveling Height Adjustment:	3 1/2" x 8" Hydraulic Cylinder
Hydraulic Hose Ends:	Standard
Jack Stand:	Standard
Hitch:	Pull Type, Parallel Clevis
Blade Carrier:	Infinity - Steel
Blades:	1/2" x 3" High Lift
Blade Overlap:	6"
HP Required:	25 - 60 PTO
Gearbox Oil (85W-140):	Factory Filled Lucas Oil
Output Shaft Diameter:	1 9/16"
Blade Tip Speed - Center 540 RPM:	13,028 FPM
Blade Tip Speed - Wing 540 RPM :	13,680 FPM
Cut Capacity:	2" Diameter
Driveline Size - Main:	CAT 4 CV
Driveline Size - Wing:	CAT 3 SC
Driveline Protection:	Slip Clutch
Deck Thickness:	12 Ga.
Side Skirt:	1/4" x 10"
Tires & Wheels (4 or 6):	RhinoTrax Foam Filled or Laminated
Wing Lift:	2" x 14" Cylinder
Wing Flex (Degrees):	90° Up / 25° Dn
Operational Wing Flex:	45° Up / 25° Dn
Safety Tow Chain:	Standard
Safety Deflectors:	Rubber Deflectors or Single Chain Guards
Tongue Weight:	720 lbs
Weight (Approx):	2,190 lbs

\* Cutting height dependent on tire size.

\*\* Gearbox rating based on field performance.

**25**  
**PTO HP**  
**MINIMUM**

**LOWER HP REQUIREMENT**  
ideal for compact tractor owners



**INFINITY STEEL**  
blade carrier protects the gearbox  
with minimal weight.



**COMPOSITE DIVIDER SHIELD**  
makes maintenance simple all while  
protecting the divider box.

