

**BUNDLE 2-5434**  
**STABILIZER BAR KIT INSTRUCTIONS**  
**FOR FORD 1110 & 1210 2WD & 4WD TRACTORS**  
**EQUIPPED WITH FORD 916A MOWER DECK**  
**AND AMEREQUIP 64Q LOADER**

The stabilizer bar can be installed on the loader mounting and mower deck using tools ordinarily available. The loader may be dismounted to ease installation (follow instructions in loader owner's manual). Shut off tractor engine and engage tractor brakes during installation.

**INSTALLING STABILIZER BAR**

1. With mower deck mounted on tractor, place stabilizer bar (1) across top of mower deck near loader mid mounting bracket so stabilizer bar reaches from valve bracket mounting plate of mid mounting bracket to ear on right side of mower deck.
2. Position stabilizer bar so that valve bracket mounting plate of mid mounting bracket is sandwiched between end plates of stabilizer bar and holes in end plates align with unused hole in bracket mounting plate. Install one 1/2 x 1-5/16" clevis pin (2) and secure it in place with a 1/8 x 1-1/4" cotter pin (3).
3. Fasten other end of stabilizer bar (1) to forward ear of mower deck in the same manner, using remaining 1/2 x 1-5/16" clevis pin (2) and 1/8" x 1-1/4 cotter pin (3).

**PARTS LIST**

Item	Part No.	Description	Qty.
1	37029	STABILIZER BAR	1
2	6021-7	PIN, Clevis, 1/2 x 1-5/16	2
3	G120123	PIN, Cotter, 1/8 x 1-1/4	2

