

# HEAVY DUTY REAR BLADES



# HEAVY DUTY REAR BLADES

- ◇ **Ditch Work**
- ◇ **Terrace Building/Maintenance**
- ◇ **General Dirt Work and Filling Ruts**
- ◇ **Snow Removal**
- ◇ **Feed Lot and Parking Lot Maintenance**



Shown with optional  
guage wheel

# HEAVY DUTY REAR BLADES

<i>Specifications</i>	<b>850</b>	<b>950</b>	<b>1540</b>	<b>2500</b>	<b>3500</b>
<b>Moldboard Width</b>	7', 8'	8', 9'	8', 10'	8', 10', 12'	12', 14'
<b>Cutting Edge</b>	1/2" x 6"	1/2" x 6"	1/2" x 6"	1/2" x 6"	1/2" x 6"
<b>Hitch Types*</b>	CAT 1 & 2 / Cat 1 & 2 QH	CAT 1 & 2 / Cat 1 & 2 QH	CAT 2 & 3 / Cat 2 & 3 QH	CAT 2 & 3 / Cat 2 & 3 QH	CAT 3 & 4 / Cat 3 & 4 QH
<b>Maximum HP - 2-Wheel</b>	90	8' = 125 9' = 95	8' = 190 10' = 160	8' = 250 10' = 225 12' = 175	N/A
<b>Maximum HP - Front Wheel Assist.</b>	70	8' = 106 9' = 81	8' = 162 10' = 136	8' = 220 10' = 200 12' = 160	12' = 300 14' = 250
<b>King Pin Diameter</b>	3" Solid Steel	3" Solid Steel	4" Solid Steel	4.5" Solid Steel	5" Solid Steel
<b>Adjustment Types</b>	Manual or Hydraulic	Manual or Hydraulic	Manual or Hydraulic	Hydraulic	Hydraulic
<b>Offset (Max.)</b>	20"	30"	37"	46"	50"
<b>Pivot Forward</b>	Up to 45°	Up to 45°	Up to 45°	Up to 45°	Up to 45°
<b>Pivot Reverse</b>	Up to 45°	Up to 45°	Up to 45°	Up to 45°	Up to 45°
<b>Tilt-Up &amp; Down</b>	Up to 15°	Up to 15°	Up to 15°	Up to 15°	Up to 15°
<b>Weight (Approx.)</b>	7' = 807 lbs. 8' = 827 lbs.	8' = 836 lbs. 9' = 876 lbs.	8' = 1,339 lbs. 10' = 1,459 lbs.	8' = 2,120 lbs. 10' = 2,260 lbs. 12' = 2,400 lbs.	12' = 3,463 lbs. 14' = 3,603 lbs.

\* Not Compatible with "Tall" Style Hitches



1020 S. Sangamon Ave. • Gibson City, IL 60936  
TEL: 800-221-2855 Option: 3 • FAX: 877-408-3298

[www.RHINOAG.COM](http://www.RHINOAG.COM)

 **MEMBER OF THE  
ALAMO GROUP**  
ALWAYS ON THE CUTTING EDGE...  
HDRB-0415-OSP



850



950



1540



2500

## BENEFITS



### Performance

- \* Rhino rear blades feature a precision-formed moldboard with the exact curvature needed to achieve maximum penetration.
- \* Rhino blades cut and roll the material instead of dragging it, saving time, horsepower, and fuel.
- \* Rhino's bolt-on cutting edges extend past the end of the moldboard slightly, reducing wear on the edge of the moldboard.



### Reliability

- \* Solid steel cold rolled kingpin on 950 and larger blades.
- \* Heavy-duty three-point hitch.
- \* Massive mainframe.
- \* Reinforced moldboard for superior strength and durability.



### Adaptability

- \* Rhino offers five series and eleven sizes of big blades ranging in moldboard widths of 7' up to 14' with maximum horsepower ranging from 85 to 300 HP to handle your demanding jobs.
- \* Adjustable height skid shoes are available for all models for working on hard surfaces.
- \* The 850, 950, and 1540 blades are available with either manual or hydraulic adjustments to match your tractor hydraulics.
- \* The 2500 and 3500 blades feature all hydraulic adjustments for greater operator convenience.



### Functionality

- \* Optional gauge wheels and quick attach end plates for maximum mobility.



3500