











REBEL SERIES

Rotary Tiller



-  All sizes available in either standard or reverse rotation
-  Designed for use on 25-65 PTO horsepower tractors
-  Six Hardened “L” blades per rotor flange
-  Cast iron gearbox housing
-  Front to rear hitch points are continuously welded to the mainframe

-  Metal debris deflector (on Reverse model only)
-  CAT 1 Standard and QH (5 & 6 ft models), CAT 1 & 2 Standard and QH (7 ft model)
-  Slip Clutch driveline protection is standard
-  1/2” Steel end plates
-  Strong “all gear” drivetrain featuring double lip seals on each end of the rotor shaft

REBEL SERIES SPECIFICATIONS

STANDARD EQUIPMENT & SPECIFICATIONS

Specifications	Standard			Reverse		
	REB60	REB72	REB84	REB60R	REB72R	REB84R
Tilling Width:	59"	70.5"	82.5"	59"	70.5"	82.5"
Overall Width:	66"	78"	90"	66"	78"	90"
Tilling Depth (Max.):*	7-1/2"	7-1/2"	7-1/2"	7-1/2"	7-1/2"	7-1/2"
Hitch:	CAT 1	CAT 1	CAT 1 & 2	CAT 1	CAT 1	CAT 1 & 2
Standard						
Quick Hitch	CAT 1 QH	CAT 1 QH	CAT 1 & 2 QH	CAT 1 QH	CAT 1 QH	CAT 1 & 2 QH
Knife Type:	"L"	"L"	"L"	"L"	"L"	"L"
Number of Knives:	42	54	66	42	54	66
Number of Flanges:	7	9	11	7	9	11
Recommended PTO HP (Min/Max):	25 / 45 HP	35 / 55 HP	45 / 65 HP	25 / 45 HP	35 / 55 HP	45 / 65 HP
Rotor Speed:	211 RPM	211 RPM	211 RPM	211 RPM	211 RPM	211 RPM
Driveline Size:	CAT 4	CAT 4	CAT 4	CAT 4	CAT 4	CAT 4
Driveline Protection:	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch
Gearbox Housing:	Cast	Cast	Cast	Cast	Cast	Cast
End Plate Thickness:	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Rotor/ Blade Rotation Dia:	17"	17"	17"	17"	17"	17"
Rotor Shaft Dia:	3"	3"	3"	3"	3"	3"
Rotor Drive Type:	Gear Driven	Gear Driven	Gear Driven	Gear Driven	Gear Driven	Gear Driven
Tine Rotation:	Standard	Standard	Standard	Reverse	Reverse	Reverse
Weight (Approx.):	673 lbs.	747 lbs.	817 lbs.	683 lbs.	759 lbs.	831 lbs.

*Requires multiple passes



Front Deflector
(Used on Reverse Model Only)



Hitch Frames Continuously
Welded to Main Frames



1/2" End Plates



1020 S. Sangamon Ave. • Gibson City, IL 60936 TEL: 800-221-2855 Option 3 •
FAX: 877-408-3298

www.RHINOAG.COM

MEMBER OF THE ALAMO GROUP
ALWAYS ON THE CUTTING EDGE™
REB-0615-OSP