

# 7026

## 26' Flex-Wing



Your Choice of CV, Equal Angle, or Parallel Ring Hitch



Hydraulic Phasing Cylinders for Level Lift



50° Divider Box Keeps Drivelines Short and Machine more Compact Front to Back



Double Acting Wing Lift Cylinders with Mechanical Float



Transport Locks for Center Section and Wings



Spring Steel Bushing at all Major Pivot Points



2-Piece Replaceable Skid Shoes on Wings



Suspension for Center and Wing Frames



10 Ga. Deck with Front Half Deck Protection Rings



A Fixed Knife Shredding Blade Kit is Available for Enhanced Shredding of Crop Residue





# 7026

## SPECIFICATIONS

### STD EQUIPMENT & SPECIFICATIONS

|                                    |  |
|------------------------------------|--|
| Cutting Width:                     | 26'  |
| Transport Width:                   | 117"   |
| Transport Height:                  | 148"   |
| Overall Width:                     | 321"   |
| Overall Length:                    | 205"   |
| Cutting Height:*                   | 1" - 14"   |
| Jack Stand:                        | HD Jack  |
| Hitch:                             | CV,<br>Equal Angle, Parallel Ring                        |
| Blade Carrier:                     | Pan or Bar   |
| Blades:                            | Flat, Updraft, Shredder                                  |
| Blade Overlap:                     | 6" (Center - Wing)<br>5" (Inside - Outside Wing)         |
| HP Required:                       | 120  |
| Tongue Weight:                     | 2400 lbs   |
| Gearbox Rating:**<br>Power Divider | 260 HP   |
| Gearbox Oil (80W-90):              | Factory Filled   |
| Output Shaft Dia:                  | 2"   |
| Blade Tip Speed:                   |  |
| Wing Outer                         | 15300 FPM  |
| Wing Inner                         | 15300 FPM  |
| Center                             | 15079 FPM  |
| Cutting Capacity (Max.):           | 2"   |
| Driveline Size:                    | 1000 RPM   |
| Driveline Protection:              | HD Slip Clutch w/ 80° CV U-Joint, Equal Angle            |
| Deck Thickness:                    | 10 Ga  |
| Side Skirt:                        | 1/4"   |
| Skid Shoes:                        | 2 Piece Replaceable                                      |
| Tires & Wheels:                    | Recapped Aircraft,<br>Light Truck Tire                   |
| Wing Lift Hydraulics:              | 3" x 30" Hydraulic Phasing                               |
| Wing Flex (Degrees):               | 45° Up/15° Dn  |
| Safety Tow Chain:                  | Std  |
| Deck Rings:                        | Std  |
| Safety Deflectors:                 | Single Chains, Double Chains,<br>Chain / Deflector Combo |
| Light Kit:                         | Std  |
| Weight (Approx):                   | 7900 lbs   |

\* Cutting Height dependent on Tire Size

\*\* Gearbox Ratings Based on Field Performance



**1 Year Limited Driveline Warranty**  
**3 Year Prorated Gearbox Warranty**

