

7026

26' Flex-Wing



Your Choice of CV, Equal Angle, or Parallel Ring Hitch



Hydraulic Phasing Cylinders for Level Lift



50° Divider Box Keeps Drivelines Short and Machine more Compact Front to Back



Double Acting Wing Lift Cylinders with Mechanical Float



Transport Locks for Center Section and Wings



Spring Steel Bushing at all Major Pivot Points



2-Piece Replaceable Skid Shoes on Wings



Suspension for Center and Wing Frames



10 Ga. Deck with Front Half Deck Protection Rings



A Fixed Knife Shredding Blade Kit is Available for Enhanced Shredding of Crop Residue



7026 SPECIFICATIONS

STD EQUIPMENT & SPECIFICATIONS

Cutting Width:	26'
Transport Width:	117"
Transport Height:	148"
Overall Width:	321"
Overall Length:	205"
Cutting Height:*	1" - 14"
Jack Stand:	HD Jack
Hitch:	CV, Equal Angle, Parallel Ring
Blade Carrier:	Pan or Bar
Blades:	Flat, Updraft, Shredder
Blade Overlap:	6" (Center - Wing) 5" (Inside - Outside Wing)
HP Required:	120
Tongue Weight:	2400 lbs
Gearbox Rating:** Power Divider	260 HP
Gearbox Oil (80W-90):	Factory Filled
Output Shaft Dia:	2"
Blade Tip Speed:	
Wing Outer	15300 FPM
Wing Inner	15300 FPM
Center	15079 FPM
Cutting Capacity (Max.):	2"
Driveline Size:	1000 RPM
Driveline Protection:	HD Slip Clutch w/ 80° CV U-Joint, Equal Angle
Deck Thickness:	10 Ga
Side Skirt:	1/4"
Skid Shoes:	2 Piece Replaceable
Tires & Wheels:	Recapped Aircraft, Light Truck Tire
Wing Lift Hydraulics:	3" x 30" Hydraulic Phasing
Wing Flex (Degrees):	45° Up/15° Dn
Safety Tow Chain:	Std
Deck Rings:	Std
Safety Deflectors:	Single Chains, Double Chains, Chain / Deflector Combo
Light Kit:	Std
Weight (Approx):	7900 lbs
* Cutting Height dependent on Tire Size	
** Gearbox Ratings Based on Field Performance	



**1 Year Limited Driveline Warranty
3 Year Prorated Gearbox Warranty**

