

RHINO®



ROTARY CUTTERS

TS12 STEALTH



- ◇ Introducing the all new TS12 Stealth Flex-Wing Cutter from Rhino.
- ◇ Designed for tractors with 35 - 60 PTO HP.
- ◇ Short turning radius for small areas.
- ◇ 1-1/2" cutting capacity.
- ◇ Low tongue weight for smaller horsepower tractor applications.
- ◇ Unique "wing-bar" blade carrier protects the gearbox output shaft with minimal weight.
- ◇ Designed for 540 RPM PTO tractors.
- ◇ Equal angle pivoting tongue and direct acting suspension system for uneven terrain.
- ◇ Smooth decks for easy cleaning and unobstructed underside for airflow through the high volume cutting chamber!
- ◇ Provides dramatic reduction in mowing time compared to most rigid deck cutters.
- ◇ Large center section skid shoes and tapered wing shoes provide anti-scalping protection.
- ◇ Chain guards included for protection.

TS12

SPECIFICATIONS

Specifications	TS12
Cut Width	144"
Transport Width	90"
Overall Width	155"
Overall Length	148"
Cutting Height	1-1/2" - 12"
Height Adjustment	Hydraulic Cylinder
Jack Stand	Standard
Blade Carrier	Wing Bar
Blades	1/2" x 3"
HP Required (Min.)	35 PTO HP
Gearbox Rating*	160 HP Divider
	65 HP Center & Wing
Output Shaft Diameter	1-9/16"
Blade Tip Speed (FPM)	14,504 Center/13,925 Wing
Cut Capacity	1-1/2" Diameter
Driveline Size	CAT 4 Equal Angle Main/Cat 3 Wing
Deck Thickness	Center: 10 Ga Bottom, 12 Ga Top
	Wings: Double 12 Ga in high stress areas
Side Skirt	1/4" x 11-1/2"
Tire & Wheel Option	Foam Filled Used Airplane Tires or Laminated Tires
Wing Lift Hydraulics	Standard
Wing Flex (Degrees)	88° Up/25° Down
Safety Tow Chain	Standard
Safety Deflector	Chain Guard
Wheel Base	126-1/4"
Tongue Weight	748 lbs
Weight (Approximate)	2,750 lbs



*Gearbox rating based on field performance.

A member of the **Alamo Group**
 1020 S Sangamon Ave, Gibson City, IL 60936
 TEL: 800-221-2855 Option 3
 FAX: 877-408-3298
www.rhinoag.com



Rhino® guarantees each piece of Rhino® equipment against defective materials and workmanship for a period of one year from date of delivery to the purchaser unless otherwise noted.

Rhino® reserves the right to make changes and/or improvements in design and construction of parts or machines shown herein without notice or obligation.



Servis and Rhino are registered trademarks of the Alamo Group Inc.