2150 15' Flex-Wings







Smooth Top and Bottom Deck Design with Dual Cut Chambers



New Composite Divider Shield



Mechancial Level Lift



Infinity Cast Carrier utilizing many of the same drivetrain components as the 3150



5 Year Limited Gearbox Warranty



New Improved Tongue Design featuring Standard Clevis



CAT 5 CV Main & CAT 4 Wing Drivelines



Coil Spring Suspension



Equip your 2150 with Rhino Trax "Foam Filled" tires or any of our 5 great tire options.



LED Lights are Standard Equipment

Specifications		2150
Cutting Width		180"
Transport Width		116"
Transport Height		75"
Overall Width		187"
Overall Length		172"
Cutting Height*		2" - 14"
Height Adjustment		Hydraulic Cylinder
Jack Stand		Standard
Hitch		Clevis
Blade Carrier		Infinity
Blades		1/2" x 4" Parallel Lift
Blade Overlap		6"
HP Required (Min)		50 HP
Gearbox Rating**	Divider Center & Wing	160 HP 130 HP
Gearbox Oil (85W-140)		Factory Filled
Output Shaft Diameter		2"
Blade Tip Speed (FF	PM) Center 540 RPM 1000 RPM Wing 540 RPM 1000 RPM	14,861 FPM 15,570 FPM 14,861 FPM 15,776 FPM
Cutting Capacity		2 1/2"
Driveline Size	Main Wing	CAT 5 CV CAT 4
Driveline Protection		Slip Clutch
Deck Thickness	Center Wing	10 Ga Top/ 7 Ga Bottom 10 Ga Top & Bottom
Side Skirt		1/4" x 12 3/8"
Tire Selections		Rhino Trax, Laminated, Pneumatic, or Foam Filled (4, 6, or 8 tires)
Wing Lift		Mechanical Level Lift
Wing Flex (Degrees))	87° Up/ 25° Down/45° Operational
Tongue Weight		1,430 lbs
Safety Tow Chain		Standard
LED Light Kit		Standard
Safety Deflector		Deflectors, Chains, or Combination
Weight (Approx)***		4,290 lbs (w/ Single Chains & 6 Rhino Trax Tires)



Smooth Top & Bottom Deck



Heavy-Duty Blades & Infinity Carrier



New Composite Divider Shield

^{***} Weight Varies with machine configuration



1020 S. Sangamon Ave I Gibson City, IL 60936 TEL: 800-221-2855 (Opt 3) I Fax: 877-408-3298





^{*} Cutting Height dependent on tire size

^{**} Gearbox Rating based on field performance