

TS10

10' FLEX-WING



Fits Through Gates as Narrow as 8'



Walterscheid EZ-Loc Collar Makes Hitch-up Easy



Replaceable Skid Shoes for Simple Maintenance



Casual Mow 4 Acres Per Hour



Smooth, Quiet Operation



Heavy-Duty Turn Buckles for More Durability and Less Stress



TS10

SPECIFICATIONS

Specifications	TS10
Cutting Width:	120"
Transport Width:	93"
Transport Height:	68"
Overall Length:	162"
Cutting Height:	1" - 15" (Dependent on Tire Size)
Height Adjustment:	3 1/2" x 8" Hydraulic Cylinder
Hitch:	Pull Type, Parallel Clevis
Blade Carrier:	Infinity - Steel
Blades:	1/2" x 3" High Lift
Tractor HP Required:	25 PTO
Cutting Capacity:	2"
Driveline ASABE:	CAT 4 CV (Main) / CAT 3 SC (Wing)
Deck Thickness:	12 Ga
Side Skirt:	1/4" x 10"
Tires & Wheels:	4 or 6, 20" Laminated, Aircraft or Foam Filled Rhino Trax
Wing Flex (Degrees):	90° Up, 22° Down
Safety Deflectors:	Deflectors or Chains
Tongue Weight:	720 lbs
Weight (Approx):	2,190 lbs

New! TS10

Flex-Wing Rotary Cutter



Unit shown with extra equipment.



*Cutting Height dependent on Tire Size.

STANDARD EQUIPMENT & SPECIFICATIONS

Cutting Width:	120"
Transport Width:	93"
Transport Height:	68"
Overall Width:	126"
Overall Length:	162"
Cutting Height: *	1" - 15"
Height Adjustment:	3 1/2" x 8" Hyd Cylinder
Jack Stand:	Std
Hitch:	Pull Type, Parallel Clevis
Blade Carrier:	Infinity - Steel
Blades:	1/2" x 3" High Lift
Blade Overlap:	6"
Tractor PTO HP Range:	25 - 60
Gearbox Oil (85W-140):	Factory Filled Lucas Oil
Output Shaft Diameter:	1 9/16"
Blade Tip Speed: Center 540 RPM Wing 540 RPM	13,028 13,680
Cutting Capacity:	2"
Driveline ASABE: Main Wing	CAT 4 CV CAT 3 SC
Deck Thickness:	12 Ga
Side Skirt:	1/4" x 10"
Tires & Wheels: (4 or 6)	See Group 2
Wing Lift:	2" x 14" Hyd Cylinder
Wing Flex (Degrees):	90° Up, 22° Down
Safety Tow Chain:	Std
Safety Deflectors:	See Group 3
Tongue Weight (Approx):	720 lbs
Weight (Approx):	2,190 lbs

TS10 is NOT intended for Commercial or Government use.

ORDERING SECTION

To order complete machine, select one item each from groups 1 - 3.
Order extra equipment as needed.

CATALOG NUMBER	DESCRIPTION	LIST PRICE (\$US)
GROUP 1A. BASE UNIT - TS10		
<i>Features 1 Year Machine Warranty & 5 Year Gearbox Warranty!</i>		
TS10-3OR1	TS10 Flex-Wing Cutter, Rhino Orange	\$10,499
TS10-3GR1	TS10 Flex-Wing Cutter, JD Green	\$10,649
TS10-3OR2	TS10 Flex-Wing Cutter, Kubota Orange	\$10,649
TS10-3RD2	TS10 Flex-Wing Cutter, Case IH Red	\$10,649
TS10-3RD3	TS10 Flex-Wing Cutter, MF Red	\$10,649
TS10-3BL1	TS10 Flex-Wing Cutter, NH Blue	\$10,649
GROUP 1B. SPECIAL EDITION BASE UNIT - TS10		
<i>Features 2 Year Machine Warranty & 7 Year Gearbox Warranty!</i>		
		
TS10-1BK1	TS10 Flex-Wing Cutter, Black Rhino Edition	\$11,999
GROUP 2. TIRE SELECTION - TS10		
00025200	Laminated 6" x 9" x 20.75"	
	4 Tires (2 Center, 2 Wing)	\$960
	6 Tires (4 Center, 2 Wing)	\$1,440
00790323	Foam Filled Used Airplane 6.75" x 10" x 20.5" - <i>Limited Time Only</i>	
	4 Tires (2 Center, 2 Wing)	\$1,184
	6 Tires (4 Center, 2 Wing)	\$1,776
00793165	Rhino Trax Foam Filled 7" x 12" x 20.5" - <i>Available June 2018</i>	
	4 Tires (2 Center, 2 Wing)	\$1,300
	6 Tires (4 Center, 2 Wing)	\$1,950
GROUP 3. GUARDING SELECTION - TS10		
00793127	Rubber Deflectors	\$539
00793128	Single Chain Guards	\$879
EXTRA EQUIPMENT (DEALER INSTALLED OPTIONS)		
00790287	2-Function Hydraulic Kit - 2 remote - wings plumbed together	\$91
00790288	3-Function Hydraulic Kit - 3 remote - all cylinders function seperately	\$150
<p>Attention: The TS10 is plumbed to require 1 tractor remote valve. Hydraulics are phased so the entire unit level lifts before the wings raise. The above kits allow hydraulic functions to be operated separately, but require 2 or 3 tractor remote valves.</p>		
REPLACEMENT ITEMS (SEE NOTE)		
<p>NOTE: The following items are listed for reference only and are available through Rhino Service Parts. See RhinoAg E-Commerce site (www.rhinoparts.com) for latest price and terms information.</p>		
Part Number	Description	
00781343	Blades, Updraft CCW	
00793152	Blades, Updraft CCW	
00793133	Blades, Updraft CW	
00786548	Blade Bolt Kit	