

RhinoAg: Single Spindles

# TW20 SERIES



Steel Infinity blade carrier



Heavy-duty tailwheel (single or dual)



2" cut capacity



Tapered side skirts to help prevent gouging



CAT 1 & CAT 2 Quick Hitch and iMatch\* compatible.



Smooth domed deck



Available in 60", 72", and 84" cutting widths



High capacity cutting chamber

\*\*iMatch is a trademark of Deere & Company.

**RHINOAG**

# TW20 SERIES

Specifications	TW25	TW26	TW27	TW27 DTW
Cutting Width:	60"	72"	84"	84"
Overall Width:	64 1/4"	76 1/4"	88 1/4"	88 1/4"
Overall Length:	108"	118"	135"	135"
Cutting Height (Min):	1 1/2"			
Hitch:	CAT 1/ CAT 2 Std. CAT 1/ CAT 2 Q.H. iMatch**		CAT 2/ CAT 3 Std. CAT 2/ CAT 3 Q.H.	
Blade Carrier:	Infinity - Steel			
Blades:	1/2" x 3"			
PTO HP Required (Min):	25	35	45	
Gearbox Rating*:	65 HP			130 HP
Blade Tip Speed (FPM):	14,335	14,963	14,369	14,369
Cutting Capacity:	2"			
Driveline Size:	CAT 3			CAT 4
Driveline Protection:	Slip Clutch			
Deck Thickness:	12 Ga			
Side Skirt:	7 Ga			
Tail Wheel:	Single			Dual
Tire and Wheel:	(1) 4" x 8" Laminated			(2) 4" x 8" Laminated
Safety Deflector:	Deflectors or Chains			
Weight (Approx): w/ Rubber Deflectors w/ Chains	720 lbs 760 lbs	800 lbs 865 lbs	1105 lbs 1180 lbs	1255 lbs 1330 lbs

\*Gearbox power rating based on actual field performance. | \*\*iMatch is a trademark of Deere & Company.

