

# RhinoAg: Flex-Wings

## 4125



Heavy-duty 12 1/2' commercial-grade rotary cutter



Ideal for commercial mowing, heavy-duty agriculture use, roadsides, and right-of-ways



Optional Orchard Package protects low-lying branches from catching in the hydraulic cylinders



Heavy-duty hinges engineered to take the daily stresses of the job



4" cutting capacity ensures nothing will stand in the way of finishing the job



Designed for tractors with 50 - 160 PTO HP



Massive, replaceable skid shoes protect the underside of the flex-wing



Independent axle suspension delivers a smoother ride and reduces wear and tear

# RHINOAG

# 4125

## Specifications

## 4125

Cutting Width	12 ½'
Transport Width	101.9"
Transport Height	73.2"
Overall Width	156.5"
Overall Length	171.2"
Cutting Height	2"-14"
Self-Leveling Height Adjustment	Hydraulic Cylinder
Hydraulic Hose End	Standard
Jack Stand	Standard
Hitch	Pull
Blade Carrier	Infinity - Cast
Blades	1/2" x 4" Parallel Lift
Blade Overlap	6"
HP Required	50 - 160 PTO HP
Gearbox Rating	160 (Divider) / 130 (Center & Wing)
Gearbox Oil	Factory Filled (85W-140)
Output Shaft Diameter	2"
Blade Tip Speed	14,504 (Center) / 14,988 (Wing)
Cutting Capacity	4"
Driveline Size	CAT 5 (Main) / CAT 4 (Wing)
Driveline Protection	Slip Clutch
Deck Thickness	10 Ga
Side Skirt	1/2" x 12"
Tires & Wheels	Foam Filled RhinoTrax or Laminated Tires
Wing Flex	90° Up / 25° Down
Operational Wing Flex	45° Up/ 25° Down
Safety Tow Chain	Standard
LED Light Kit	Standard
Safety Deflectors	Chain Guards
Wheel Base	147"
Tongue Weight	1,200 lbs
Weight (Approx)	4,000 lbs



### WHEEL SUSPENSION

Independent axle suspension delivers a smoother ride and drastically reduces wear and tear.



### ORCHARD PACKAGE

An optional bolt-on shield to protect low-lying branches from catching in the hydraulic cylinder.

## WARRANTY

**1 YEAR MACHINE**  
**2 YEAR LTD DRIVELINE**  
**6 YEAR LTD GEARBOX**  
**2 YEAR SEALS**

